40

with read recording [illegible]

(a)

Electron Beam Deposition of Circuits

The following arrangements have been conceived for de-
depositing electronic circuits onto bases



FIG. 1

J. Lewis

[illegible] MATTER READ & UNDERSTOOD

BY [illegible] DATE [illegible]

EXHIBIT A - SN. 696,747



Fig. 24



12

In the electron beam apparatus Fig. 1 pp. 140 & 141 the casing for which I have been working on over the past 10 months it is noted that:

(1) The beam may be deflection controlled by means of an analog signal or signals using deflection plates of conventional design

(2) ~~The beam focus~~ All servos such as door ~~etc~~ vac. chamber opening & closing servo, work positioning servo, ~~and~~ servos for feeding material into the beam manipulator for admitting and removing workpiece from chamber, work clamping servo, etc as well as the means for controlling focus, deflection, and selection of (one of a multiple of) beam may be automatically controllable in automatic cycle of operation by means of a programming means such as a magnetic or other recorder on which is recorded the necessary analog and/or digital signals to effect said control which record is operated and transduced from to derive said signals in a predetermined sequence -

(3) Material to be deposited may be admitted to beam as a rod or wire, powder, liquid, vapor or gas which materials are carried along by beam to its work piece and focused thereon by beam. Beam energy or modulation may be controlled by a reproduced analog or digital signals to prepare (heat or erode, melt or vaporize) surface or surface on which selected deposits are to be made.

(4). Chemical reactions, alloying, doping, etc may take place on beam of by means of beam and material therein deposited on or diffused into surface intersected by beam.

THIS CONFIDENTIAL MATTER READ & UNDERSTOOD

BY _____ DATE _____

THIS CONFIDENTIAL MATTER READ & UNDERSTOOD

BY _____

THIS CONFIDENTIAL MATTER READ & UNDERSTOOD

BY _____ DATE _____

machining or otherwise physically
chemically changing material deposited
eam may be effected by change of
beam energy, etc or by means of
more auxiliary beams generated
e same gun or chamber (different guns)
are auxiliary deflection controlled and
ted.

terial to be deposited (wire, powder, vapor,
quid) may be positionally controlled by
o or series controlled by the programming
controlling the other variable to be
flowed or moved into the volume
focus of the beam directly above surface
M.

eam may be focused in gun onto which
material is selectively fed and controlled
he programming means, after beam
be diverged or directed as a narrow
against surface of work and/or deflectionally
ed.

illiary beams may feed into main beam
after or at its focus or near its generation
which auxiliary beams contain atoms of
al to be deposited onto surface by
beam which may be deflection controlled
ter in accordance with a programmed

e optical maser may be used as or
iary beam generator in conjunction with
arrangements or in place of electron
generating means used. Maser beam
be travelled inside or parallel to electron beam
ns or may be directed at the focus
electron beam to cooperate in machining
removing depositing surface of work or evaporating
terial to be fed by beam.

INITIAL READ & UNDERSTOOD

INITIAL READ & UNDERSTOOD

DATE

Beam Deposition Continued 15



Fig. 7 Side sectioned



Side Sectional



All deposits are by beam controlled by analog signals reproduced from a recorder which recorders programmed signals (reproduction) also control material selection (int into beam, rate of flow there travel of beam across work and on-off of beam, positi workpiece, handling of wo within and in and out of vacuum chamber, etc.)

Feedback signals for indicating how much ma is deposited and where to control beam position flow and selection of ~~is~~ different materials to be admitted to beam may be effected by means a reading electron beam directed by computer or programmed (recorded signals) to scan selected area by scanning entire target as the mat is deposited or during periods when materi

16R. 6f

THIS CONFIDENTIAL MATTER READ & UNDERSTOOD

BY _____ DATE 11/24

THIS CONFIDENTIAL MATTER READ & UNDERSTOOD

BY _____ DATE _____

t being deposited (inspection scanning period). The
ut video signal derived by beam scanning
y be analyzed by techniques as described in
pending application "Automatic Inspection System"
digitally determining in digital form the
aracteristics (optical characteristics) of the material
osited.

Spectroscopy may also be employed in
ich a beam is directed against the deposited
a and causes an emission of electrons therefrom
ich is spectrally analyzed, the results of
hich are used to control further deposition
moval of deposited material.

by
Ernest W. Waldmeyer 11/1/

THIS CONFIDENTIAL MATTER READ & UNDERSTOOD
TC

Material from p. 138
to this point read by
Isidore Math on
11/1/

Classification of Electron Beam Deposition apparatus
d Methods.

The following are arrangements, apperatus and methods
e conceived relating to electron beam manufacture of micro-
ature circuits which I intend to incorporate in a number of
nt applications.

Deflection and intensity control of deposition (or machining, welding,
electron beam or beams attained by one of the following techniques
(a) Reproduced magnetically recorded video picture signal or signals.
(b) video signal generated by scanning optical recording
(c) output of digital recorder
(d) output of comparator (summing amplifier) fed (a) or (b) above
plus feedback signal generated by scanning either or both
beam containing deposition material or surface containing
posited material.*

Correction for over or incorrect area deposition may be made
controlling beam per-se (by computer command signals or
tput of summing amplifier being fed command reproduced video
gnal and feedback scanning signal) which beam either

machines or vaporizes material already deposited.**
** Vaporized material (vaporized by corrective beam) may
removed from surface of workpiece by another beam
deflection controlled or otherwise positioned to effect said
removal.

Correction for over deposition may also be made
deflection controlled beam containing an oxidizing or other
for chemically changing part of deposited material to a
compound.

Work may be positionally controlled by command sig
derived from command recording as described or compa
receiving command and feedback signals as described.

II Deflection control of beam (x, y position plus
intensity modulation plus position of focus (z contr
depending on position of the surface being scan-deposited on
(a) depositing semi-conductor, metal or dielectric mate
(b) depositing plural materials simultaneously different
(c) " " " "
(d) introducing different materials at different times by differen
single feeder. at same or different ti
(e) welding, machining, vaporizing deposited material

III Feedback signal compared with reference command (repr
(beam control signal) is generated by:
(a) Beam scanning and analysis of ionized or vaporized particle
therein as beam is generated and material(s) admitted there
(b) optical beam or work scan plus analysis
(c) Spectroscopy or spectrographic (automatic) analysis
mass spectrograph + scan.
(d) Electron beam scan of deposited work with a vide
read beam.

IV Material feed (to beam) by and as:
(a) Rod or wire, servo driven into beam, into intermediary
electrode generating beam (into orthogonal electrodes) or directly into
of beam at work; servo controlled by direct command or co
output receiving reproduced command signal plus feedback signal.
(b) Servo controlled powder feed (as above) feedback signal.
(c) Servo valve controlled (as above) feed of liquid conta

ction material into beam (or vaporized deposition
rial into beam).

Plural Beams

Plural reproduced deflection control signals plus
rial control or reference signals, plus work positioning
als (optional), plus focus adjustment signals (optional)
others mentioned above are used to simultaneously
quentially control beams each depositing different material
aterials

Beam Deposition Techniques (Miscellaneous features)

(a) Electron beam plus photographic techniques.

(1) Beam deposits components onto conducting film pattern
formed by photo-etching, photocomposition (exposure to light
and developing)

(2) Optical beam (laser light beam) is deflection controlled
and cooperates with deflection controlled electron beam
in welding, machining, effecting deposition, chemically
reacting on deposited materials) deposited by electron beam, etc.
Laser light beam may also be used to carve photosensitive
film, expose it per se, develop image, used for corrective
purposes (vaporize or machine material (film) deposited
by electron beam, vaporize material(s) to be
deposited or directed by electron beam, abide work, etc.
Laser beam deflection controlled by servo controlled
mirror(s) controlled by reproduced command signal
or output of comparator or computer.

(b) Plural beams cooperate. One vaporizes (laser or electron
am) material to be deposited, feeds it at or to second deposition
n, there which is deflection controlled and deposits material,
d beam scans either second beam or surface which
s just received material to provide a feedback signal
a comparator (summing amplifier or other) which
vides an output to control both first and second
eams (i.e. on-off or intensity or focus of first beam
d position of second beam) (c) First and second beams
e controlled by respective command signals fed to

48

well by passing beam thru mask

respective comparator means each of which receives same feedback signal generated by beam begin scanning what is being or was just deposited

(c) An apparatus for repairing, modifying or adding micro-miniature circuitry has also been conceived based on beam scanning the circuit already deposited (surface scanning) and determining by reading with the beam the physical-optical or atomic structure of the circuit, by x-ray scanning, by optical scanning said circuit (with a modulated light beam) or by a combination of two or three of these scanning techniques, as been conceived. The output signal derived by scanning is fed to a computer which thereafter provides signals for controlling beam deflection, modulation, position of workpiece, material selection and feed to beam, mask selection, etc to effect a desired repair, change in structure, etc

(d) Vaporization of material in a primary electron be or by means of a molten through which beam(s) the deposito beam is passed and picks up the material to be deposited, carries

(e) Material changed by, new composition(s) formed in a beam directed against a workpiece by either the action of the beam per se or the reaction of the beam (temperature, e and two or more of the materials admitted thereto or one o more admitted material and material of the workpiece.

(f) Growth of predetermined crystal structure by means of fe melting material(s) admitted thereto and deposited, or by a combination of materials admitted to beam being deposi thereby onto a crystal being grown. Programmed control of beam deflection, on-off-modulation, focus; crystal moveme material flow into beam (based on feedback derived by sc beam, crystal, etc. (as described above) fed into comparator also a command signal and providing difference signal for contro

(g) Creation of mask through which erosion, election bea is directed to chemically and/or mechanically affecting (e changing chemically, welding, etc) the workpiece by means of photosensitive mask material, thermoplastic recording film of General Electric Co. which mask is formed by exposure to a writ beam of said mask material which writing beam is modu to affect the desired image (transparent and opaque or reg pattern in the mask. Mask may be in the field of the

sted against the workpiece (in path of beam)
(b) Use of a unique mask in beam path made of a grating - as a diffraction grating produced by beam etching thin plate selective and controlled deposition of material introduced in beam or to or after passing thru mask. Plural diffraction gratings used at right angles to each other will produce line beams ~~s~~ than .001 inches in diameter.
(c) Use of a mask to break up beam intense electron or laser m into a plurality of beams directed thereafter against lected areas of the workpiece for ~~etc~~ effecting welding, ~~a~~ching (hole drilling), erosion or deposition onto said select s.
(d) Program control (plus feedback where necessary) of beam tion (deflection), focus, ~~etc~~ & position of workpiece, and fferent material fed into beam to selectively deposite ferent material onto different areas of workpiece.
(e) Exposure, machining, chemically changing, development and ng of a photosensitive material to form a circuit by means ~~f~~dam and use of beam to deposit semi-conducting, dielectric onducting materials onto selected areas of photosensitively develope cuit all by automatic control as above.

J. Mullen

C.I.

PAGE 150 - IS MISSING

Extrude multiple sheets or strips apart + filaments of different materials) + laminate continuously.

to rods, tubes, wires or other structural members made of plastic filaments or metal whiskers (single crystals of metal of exceptional strength) which are compacted together and bonded or welded where they cross. They may be encapsulated in another plastic, metal, sintered powdered metal, etc to form solid, filament reinforced structures.

It is conceived to simultaneously extrude a plurality of sheets of thermoplastic or ribbons thereof from a single die but from spaced-apart slot openings and guide said sheets or strips as follows continuously:

(a) First guide apart and admit filaments (reinforcing or decorative), or cloth, threads or other material as a continuous or broken web between two of said strips and continuously laminate into a single, integral sheet of reinforced material

(b) Draw each sheet thru polishing rolls and then laminate (improved clarity).

(c) Simultaneously extrude from another extrusion chamber, a plurality of reinforcing filaments (of glass, polypropylene, or other plastic), guide these between at least two of the strips, or ribbons or sheets not extruded and continuously laminate together by



J Lemelson

Material from p 145 to this point read + understood by me this 4th day of

A Serlin

61